

C. Concl.
Sub D
C2

(d) control means for controlling the condition information so as to be copied from said second memory means to said first memory means in order to control the condition of the image signal pickup by using the condition information.

7. (Twice-Amended) An [imaging] image pickup apparatus, comprising:

- (a) image pickup means;
- (b) first memory means for storing an image signal outputted from said image pickup means;
- (c) second memory means capable of storing the image signal outputted from said image pickup means, said second memory means being detachably attached to said apparatus;
- (d) signal processing means for performing a processing on the image signal on the basis of condition information representing a condition in which the image signal is picked up by said image pickup means, each of said first and second memory means being capable of further storing the condition information; and
- (e) control means for controlling the condition information so as to be copied from said second memory means to said first memory means in order to control the condition of the image signal pickup by using the condition information, [;]
said control means including switching means for switching an operation of said control means between a plurality of operation modes.

C3 35. (Amended) An electronic apparatus comprising:

- (a) ~~signal inputting means;~~
- (b) first memory means capable of storing a first signal output from said signal inputting means and a second signal representing a condition in which the first signal is [recorded] inputted by said signal [recording] inputting means;
- (c) second memory means capable of storing the first signal and the second signal, said second memory means being detachably attached to said apparatus; and
- (d) control means for controlling said second signal so as to be copied from said second memory means to said first memory means and for controlling said signal inputting means so as to input said first signal by using said second signal.

[Please enter the following additional claim.]

C4 37. An image pickup apparatus comprising:

- (a) ~~image pickup means;~~
- (b) memory means capable of storing an image signal output from said image pickup means and condition information representing a condition in which the image signal is picked up by said image pickup means, said memory means being detachably attached to said apparatus; and
- (c) control means for controlling said image pickup means so as to allow image pick up by using said condition information stored in said memory means.